



The difference between conventional designs and the space-coiled MPPs design

## Technology Summary

Penn State researchers developed a sound-absorbing panel that can achieve broader frequency ranges of high acoustic absorption. The panel has a specific thickness thinner than the structures of conventional porous sound absorption materials and micro-perforated panels (MPP). A unit cell within the panel collectively absorbs noise with a certain range of frequency. Different unit cells are combined to create a supercell that provides a plurality of resonant modes for broadband sound absorption.

## Application & Market Utility

A sound absorber with broadband and high absorption at a deep-subwavelength scale is applicable to many fields, such as room acoustics, automobiles, and aerospace engineering. Currently, to achieve a deep-subwavelength scale, a thin decorated membrane is used as well as a modified geometry of the conventional porous sound absorption material and microperforated panel. Those strategies have relatively narrow absorption bandwidth which hinders practical applications. This design, which consists of a combined supercell structure, can achieve broader frequency ranges from 20 Hz to 6 kHz.

## Next Steps

The inventors are pursuing a possible licensing opportunity.

### TECHNOLOGY READINESS LEVEL

4

#### Seeking

Investment | Licensing |

#### Keywords

- Sound absorbing panel
- Space-coiled cavities
- Broadband
- Deep-subwavelength scale
- Metamaterial

#### Researchers

##### Yun Jing

Professor

[Website](#)

##### Jun Ji

Graduate Student

##### Originating College

College of Engineering

#### Office of Technology Management Contact

Joseph Rokita

[jjr152@psu.edu](mailto:jjr152@psu.edu)

814-863-6336